

1N 220-240V 50/60Hz - 1x 16A 

1 fase - 1 nul


1 phase - 1 neutral

1 Phase - 1 Nullanschluss

1 phase et 1 neutre

Aderdoorsnede
Aderquerschnitt
Cross sectional area
Fil diamètre

3x2,5 mm²



Max 3720W



2-2N 230V 50Hz - 2x 16A 

2 fase - 2 nullen


2 phases - 2 neutral

2 Phasen - 2 Nullanschlüsse

2 phases et 2 neutres

Aderdoorsnede
Aderquerschnitt
Cross sectional area
Fil diamètre

5x2,5 mm²



only NL/alleen NL

2N 380-415V 50/60Hz - 2x 16A $\Rightarrow$

2 fase - 1 nul

2 phases - 1 neutral

2 Phasen - 1 Nullanschluss

2 phases et 1 neutre


Aderdoorsnede

Aderquerschnitt

Cross sectional area

Fil diamètre

4x2,5 mm²



1N 220-240V 50/60Hz - 1x 32A $\Rightarrow$

1 fase - 1 nul

1 phase - 1 neutral

1 Phase - 1 Nullanschluss

1 phase et 1 neutre

Aderdoorsnede

Aderquerschnitt

Cross sectional area

Fil diamètre

3x4 mm²

