


2-2N 230V / 50 Hz 2x16A

1N 220-240V 50/60Hz - 1x 16A ⇐

- 1 fase - 1 nul
- 1 phase - 1 neutral
- 1 Phase - 1 Nullanschluss
- 1 phase et 1 neutre

Aderdoorsnede
Aderquerschnitt
Cross sectional area
Fil diamètre

3x2,5 mm²




Max 3500W | setting 2_3

3N 380-415V 50/60Hz - 3x 16A ⇐

- 3 fase - 1 nul
- 3 phases - 1 neutral
- 3 Phasen- 1 Nullanschluss
- 3 phases et un neutre

Aderdoorsnede
Aderquerschnitt
Cross sectional area
Fil diamètre

5x1,5 mm²




1N 220-240V 50/60Hz - 1x 32A ⇐

- 1 fase - 1 nul
- 1 phase - 1 neutral
- 1 Phase - 1 Nullanschluss
- 1 phase et 1 neutre

Aderdoorsnede
Aderquerschnitt
Cross sectional area
Fil diamètre

3x4 mm²




2N 380-415V 50/60Hz - 2x 16A ⇐

- 2 fase - 1 nul /
- 2 phases - 1 neutral
- 2 Phasen - 1 Nullanschluss /
- 2 phases et 1 neutre

Aderdoorsnede
Aderquerschnitt
Cross sectional area
Fil diamètre

4x1,5 mm²




2-2N 230V 50Hz - 2x 16A ⇐

- 2 fase - 2 nullen
- 2 phases - 2 neutral
- 2 Phasen - 2 Nullanschlüsse
- 2 phases et 2 neutres

Aderdoorsnede
Aderquerschnitt
Cross sectional area
Fil diamètre

5x1,5 mm²



only NL/alleen NL